

AIROMAX.NET

CALL 514-567-OMAX

AR-2000F / 2400F

- 3 Ply Construction
- Asbestos-Free E-Glass Base Fabric
- Woven Insulating Fiberglass Filler
- Stainless Steel Mesh Interior
- Exterior Stainless Steel Helix
- Abrasion & Cut Resistant
- Water Repellent
- Excellent Mineral Oil Resistance
- No Glues or Adhesives
- Extremely Flexible
- High Temperature Resistant
- Standard 25ft Lengths
- Custom Lengths Available on Request



TECHNICAL DATA:

Colour & Coating	Red/Brown
Base Fabric	Cross Twill E-Glass Reinforced with V4A Wire
Filler	Woven Fiberglass
Core	Fine Stainless Steel Mesh
Helix	Stainless Steel
Compression Ratio	3:1
Temperature Resistance - Cold	-40° F (-40° C)
Continuous Operating Temperature - Hot	+2000° F (+1100° C)
Intermittent Operating Temperature - Hot	+2400° F (+1315° C)

SUGGESTED APPLICATIONS:

AR-2000F high temperature flexible consists of 3 tier construction - combining a polyurethane coated E-Glass fabric reinforced with wire; woven fiberglass filler and fine stainless steel mesh. All tiers are interlocked with a stainless steel external helix and reinforced with hard-drawn steel wire filler. This product is rated for extremely high temperatures, water repellent and offers improved hydrolysis and mineral oil resistance. The AR-2000F is ideal for diesel exhaust, high temperature fume extraction, and a wide range of other extreme service applications. The temperature range of AR-2000F is -40° F to +2000° F (-40° C to 1100° C). The base material is oven tested and offers good UV resistance.

AIROMAX PROPRIETY